

SRS CALIBRATION FLUID CV

Description:

Calibration fluid for diesel injectors

SRS CALIBRATION FLUID CV is a low viscosity test oil for the calibration of diesel injection pumps, with a very low viscosity tolerance. It has an excellent protective power against wear and corrosion and poor foaming tendency.

SRS CALBRATION FLUID CV meets ISO 4113-CV-AW standards.

SRS CALIBRATION FLUID CV is recommended by Bosch (VS 15665-OL) and Daimler-Benz (approval MB 133.0). In addition, it has been approved by MTU as an anti-corrosion protection for the internal protection of power supply systems.

- Approval MB 133.0
- MTU approval as corrosion protection for internal protection or preservation of power systems
- Standard Bosch VS 15665-OL-CV
- Standard ISO 4113-CV-AW

SRS CALIBRATION FLUID CV is a product of H&R Chem Pharm GmbH. manufactured in Germany.

AVERAGE PHYSICAL AND CHEMICAL CHARACTERISTICS *

Density at 20°C	ASTM D 1298	Kg/lit	0,823
Viscosity at 20°C	DIN 51 562	cSt	3,85
Viscosity a 40°C	DIN 51 562	cSt	2,50
flash point	DIN EN 22 719	°C	115
Cloud point	ASTM D 2500	°C	-28
Initial boiling point	DIN 51 751	°C	232
final boiling point	DIN 51 751	°C	265
Corrosion test on steel	DIN 51 585	level	0 - A
Corrosion test on copper	DIN ISO 2160	level	1
Corrosion test in humidity chamber	DIN 51 359	level	6 x 0

* the reported data are not specific