

IPC600

Simulatori EUI/EUP
EUI/EUP Simulators



IPC600 è il nuovo Cam Box Rabotti. Un sistema a camme multiple permette una perfetta diagnosi dei sistemi d'iniezione EUI/EUP multibrand.

Adattabile a qualsiasi banco tradizionale, permette secondo specifiche OEM la rilevazione del BIP e del tempo di risposta, oltre che la generazione della codifica Delphi E3. È la soluzione più completa per la moderna officina Diesel dei mezzi industriali.

IPC 600 is the new Rabotti Cam Box. A system of multiple cams that allows a perfect diagnosis of EUI/ EUP multibranded injection's systems.

Adaptable to any traditional bench, it allows according to OEM specifications the detection of the beep and the response time, as well as the generation of Delphi E3 encoding. It's the more complete solution for the modern Diesel workshop of industrial vehicles.

DIMENSIONS AND WEIGHT

Cam Box Dimensions (W x L x H)
490 x 250 x 810 mm

Electronic Unit Dimensions (W x L x H)
435 x 510 x 170 mm

Cam Box Weight
70 kg

Electronic Unit Weight
20 kg

FLOW SENSORS FEATURES

Flow Range
1 ÷ 4000 cm³ / min

Load Cell
n° 1 with Range = 0 ÷ 22 kN

ELECTRICAL DATA

Electrical Socket
2P + GND

Voltage - Frequency - Amperage
230 / 120 V - 50 / 60 Hz - 4 / 7 A

Power Required
1,5 kW

OTHER DATA

Power Required by the Motor
Starting from 7,5 kW

Begin Injection Period
Measurement of BIP

Coding Features
Delphi

TEST OIL

Oil Type
DIN ISO 4113

Oil Lubrication Cam Box
10W40