

DIESEL EQUIPMENT

RABOTTI IPC600

IPC 600 is the new Rabotti Cam Box. A system of multiple cams that allows a perfect diagnosis of EUI/ EUP multibranded injection's systems.

Adaptable to any traditional bench, it allows according to OEM specifications the detection of the beep and the response time, as well as the gene ration of Delphi E3 encoding. It's the more complete solution for the modern Diesel workshop of industrial vehicles.

Dimensions and weight

FEATURE	VALUE
Cam Box	490 × 250 × 810 mm — 70 kg
Electronic Unit	435 × 510 × 170 mm — Peso: 20 kg

Flow sensors features

FEATURE	VALUE
Flow Range	1 ÷ 4000 cm³/min
Load Cell	1 with range 0 ÷ 22 kN

Electrical data

FEATURE	VALUE
Electrical Socket	2P + GND
Voltage - Frequency - Amperage	230 / 120 V - 50 / 60 Hz - 4 / 7 A
Power Required	1,5 kW

Rabotti S.r.l.
P. IVA IT01365710035

Via Capponi 13,
10148 Torino (IT)

+39 011 2297836 / 842
sales@rabotti.it

Other data

FEATURE	VALUE
Power Required by the Motor	Starting from 7,5 kW
Begin Injection Period	Measurement of BIP
Coding Features	Delphi

Test oil

FEATURE	VALUE
Oil Type	DIN ISO 4113
Oil Lubrification Cam Box	10W40

Rabotti S.r.l.
P. IVA IT01365710035

Via Capponi 13,
10148 Torino (IT)

+39 011 2297836 / 842
sales@rabotti.it